

## WO0161965

Publication Title:

AUTOMATIC SWITCHING NETWORK POINTS BASED ON CONFIGURATION  
PROFILES

Abstract:

Abstract of WO0161965

A method and apparatus to reconfigure parameters for establishing a link with a new host after a computer is moved to a new location or a new network.

Data supplied from the esp@cenet database - Worldwide

-----  
Courtesy of <http://v3.espacenet.com>

BEST AVAILABLE COPY

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
23 August 2001 (23.08.2001)

PCT

(10) International Publication Number  
**WO 01/61965 A1**

(51) International Patent Classification<sup>7</sup>: **H04L 29/06**

[MY/US]; 10309 Glencoe Drive, Cupertino, CA 95014 (US). **ZHANG, Yadong** [CN/US]; 46716 Crawford Street, #5, Fremont, CA 94539 (US).

(21) International Application Number: PCT/US01/04829

(22) International Filing Date: 14 February 2001 (14.02.2001)

(74) Agents: **KIRKLAND, Mark** et al.; Fish & Richardson P.C., 2200 Sand Hill Road #100, Menlo Park, CA 94025 (US).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/182,391 14 February 2000 (14.02.2000) US  
09/569,576 10 May 2000 (10.05.2000) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(71) Applicant (*for all designated States except US*): **SYGATE TECHNOLOGIES, INC.** [US/US]; 6595 Dumbarton Circle, Fremont, CA 94555 (US).


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **YEAP, Yuen-Pin**

[Continued on next page]

(54) Title: AUTOMATIC SWITCHING NETWORK POINTS BASED ON CONFIGURATION PROFILES



(57) Abstract: A method and apparatus to reconfigure parameters for establishing a link with a new host after a computer is moved to a new location or a new network.

WO 01/61965 A1



IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

## AUTOMATIC SWITCHING NETWORK POINTS BASED ON CONFIGURATION PROFILES

### CROSS-REFERENCE TO RELATED APPLICATIONS

5        This application claims the benefit of the earlier filing date of U. S. Provisional Application No. 60/182,391, filed February 14, 2000, which is incorporated herein by reference.

### TECHNICAL FIELD

10        This invention relates generally to providing wireless network access, and more particularly to automatic reconfiguration of hardware and network parameters for a mobile computer in a wireless network.

### BACKGROUND

15        There are growing demands for mobile Internet access. Conventional computer systems are commonly configured in local area networks. A mobile computer may use a standard PCMCIA network card to connect to the local area network. The PCMCIA network card typically includes a telephony modem that can be physically connected by network cable to a telephone line. Once connected, nodes within the network communicate with one another through air and space using radio, microwave, and infrared frequencies in the megacycle/second or kilomegacycle/second ranges, or through  
20        other well-known techniques in the field such as point-to-point laser systems. However, the network cable connection restricts the computers' mobility because these computers need to be physically connected to a "hub" or "port."

25        One promising solution for providing network access to mobile computers is the Wireless Network Interface Card (WNIC). The WNIC eliminates the need for network cables, and thus allows for more user mobility. Armed with a WNIC, a node in the wireless network, such as a notebook computer, can be as far as 150 feet away from the rest of the network, depending on the composition and thickness of the walls in the building where the wireless local area network (WLAN) is deployed. The WNIC cards communicate with one another through radio waves, and the transmission rate can be as  
30        high as 11 Mbps.

      The WNIC works in two modes: infrastructure mode and *ad hoc* mode. In the infrastructure mode, a WNIC communicates with the network through an Access Point (AP) devices. In the *ad hoc* mode, the WNIC's communicate with one another directly without using AP devices.

35        Despite the mobility, nodes equipped with a WNIC still face problems regarding

hardware and network configurations. When a mobile computer moves between multiple AP devices, or switches from infrastructure mode to *ad hoc* mode, the mobile computer is typically disconnected and then reconnected. The mobile computer subsequently needs to be manually reconfigured by the user for proper connection to a new system. Therefore, there exists a need for a method and apparatus to automatically reconfigure the WNIC contained within a computer when the computer moves between AP devices within a network, and/or when the computer moves outside the network to connect to a different network.

### SUMMARY

This invention provides user mobility in reconfiguring the network environment as a user moves to locations controlled by different AP devices within a wireless local area network (WLAN), or as the user moves to different locations not necessarily within the same WLAN. A system is provided that constantly scans the wireless network environment to detect changes in an existing AP device or the presence of a new AP device. The system automatically reconfigures the wireless hardware parameters and network configuration parameters when it detects changes in the quality of an established link by selecting a most suitable working profile in a profile database. By combining auto-sensing and the user profile management system, the system alleviates the need for users to manually adjust their configuration in order to communicate with a network when it encounters multiple AP environments.

In one aspect, the invention features a method to configure parameters after a computer is moved to a new location. The method includes steps of examining an established link for a need to establish a new link, establishing the new link by selecting a network profile from a plurality of network profiles stored in a profile database, the network profile containing a plurality of configuration parameters for establishing links, and reconfiguring parameters for a current network setting automatically without user input.

In another aspect, the invention is directed to an apparatus having a computer-readable storage medium tangibly embodying program instructions for configuring a computer after the computer is moved to a new location, the program instructions including instructions operable for causing a computer to examine an established link for a need to establish a new link. To establish the new link by selecting a network profile from a plurality of network profiles stored in a profile database, the network profile having a plurality of configuration parameters for establishing links, and reconfigure a

current network setting.

In yet another aspect, the invention is directed to a computer readable memory which includes a reconfiguration apparatus consisting of a profile database to store a plurality of network profiles containing reconfiguration parameters for reconfiguring a network environment for a node in a network after the node is relocated to a different location. A detection process to examine the quality of an established link on a node, and a selector process, operatively coupled to the profile database to select in response to a signal from the detection unit, a next profile from the profile database for establishing a suitable network environment for the node. The plurality of network profiles may be stored by priority in the profile database.

In another aspect, the invention is directed to a computer readable memory which includes a reconfiguration apparatus having an auto-sensing process to detect changes in a network environment by checking for a connection, an AP device and a quality of the connection, and a user profile management process to step through automatically a plurality of parameters associated with a selected profile to communicated with the network based on plurality of parameters.

Various implementations of the invention may include one or more of the following features. The method where the examining step may be repeated once every three seconds. The establishing step may include testing each network profile from the plurality of network profiles until the new link is established. The establishing step may include establishing the new link with an access point including issuing a soft boot command or new link with a wireless card. The reconfiguring step may further consist of searching for a dynamic TCP/IP setting for a current location, and if found, releasing and renewing a current IP. It may receive and return packets from and to a wireless card driver. The program instructions further may have instructions to cause the computer to examine the established link once every three seconds, it may have instructions to cause the computer to test each network profile from the plurality of network profiles until the new link is established. The program instructions may have instructions to cause the computer to establish the new link with an access point by issuing a soft boot command or a new link with a wireless card. The program instruction may cause the computer to reconfigure and may search for a static TCP/IP setting for a current location, it may release a current IP, renew the current IP, and may receive and return packets from and to a wireless card driver. The reconfiguration parameters may have SSID, associated address and channel, IP address, subnet mask, and gateway. The parameters may further have a

domain name and DNS address. The node may communicate with other nodes in the network through access points or in an *ad hoc* mode. The node may support encrypted information and the node may run in power saving mode. Aspects of the invention can include one or more of the following advantages. A system is provided that eliminates the need for manual modifications of the WNIC hardware and network parameters when a node on the wireless network is moved. Manual reconfiguration of the parameters is a tedious process, and the automation of this process will undoubtedly increase the popularity of the use of WNIC's in the future. The system is versatile, in that the automatic reconfiguration is not only provided when a node connects to a different AP device within the same network, but also when a node moves outside the network, or connects to the network without an AP device.

The details of one or more embodiments of the invention are set forth in the accompanying drawings and the description below. Other features, objects, and advantages of the invention will be apparent from the description and drawings, and from the claims.

### DESCRIPTION OF DRAWINGS

FIG. 1 is a schematic drawing of network configurations suitable for automatic reconfiguration of software/network connection parameters.

FIG. 2 is a block diagram illustrating the various interactions of the software and hardware components of the system of FIG. 1.

FIG. 3 is a screen shot of a reconfiguration dialog box.

FIG. 4(A) is a screen shot of the first of the two dialog boxes for adding a new profile.

FIG. 4(B) is a screen shot of the second of the two dialog boxes for adding a new profile.

FIG. 5 is a flow chart illustrating a method for automatically reconfiguring the parameters of a node in a LAN as it moves locations within or without the LAN.

FIG. 6 is a block diagram illustrating exemplary computer hardware components that constitute a suitable environment within which the principles of the present invention may be implemented and operated.

Like reference numbers and symbols in the various drawings indicate like elements.

### DETAILED DESCRIPTION

Mobile computers can gain wireless access to network resources through the use

of a Wireless Network Interface Card (WNIC). The WNIC's communicate with each other through radio waves, and some vendors can provide cards at a transmission rate as high as 11 Mbps, which is equal to or better than a thin Ethernet connection which typically transmits at 10Mbps. The WNIC works in two modes: infrastructure mode and  
5 *ad hoc* mode.

In the infrastructure mode, a WNIC communicates with the network through Access Point (AP) devices. The AP device can communicate in both the wireless radio wave environment and the traditional Ethernet environment. Multiple WNIC's can communicate with each other through AP devices. In the *ad hoc* mode, the WNIC's can  
10 communicate with each other directly, but they cannot communicate with computers that have only Ethernet adapters. Operating in either mode, a WNIC provides a true wireless network access capability for mobile computers.

FIG. 1 illustrates network environments in which the method and apparatus of this invention can be used to reconfigure parameters as a mobile unit changes locations. In  
15 the implementation shown, a wireless network 100 consists of two cells, cell 110 and 112. In one implementation, the wireless network 100 is compliant with the Institute of Electrical and Electronics Engineers (IEEE) 802.11 standard, which allows for wireless integration with wired IEEE 802.3 Ethernet networks using devices called access points or base stations. The fundamental building block of the 802.11 architecture is the cell,  
20 also known as the basic service set (BSS) in 802.11 parlance. A cell typically includes one or more wireless stations and an access point. For example, cell 110 includes two wireless stations 114 and 116 and an AP device 118, and cell 112 includes the wireless stations 122 and 124 and an AP device 120. The nodes, or wireless stations, and the access point device communicate amongst themselves using the IEEE 802.11 wireless  
25 MAC protocol. Multiple AP devices may be connected together, either through a wired Ethernet or another wireless channel, to form a so-called distribution system (DS). The DS appears to upper level protocols (e. g., IP) as a single 802 network, in much the same way that a bridged, wired 802.3 Ethernet network appears as a single 802 network to the upper layer protocols. Here, the AP device 118 and AP device 120 are connected to the  
30 ports of hub 126, which is connected to LAN 128 and then to Internet 130. Hub 126 may support other computers not in network 100, such as independent server 148.

In a typical wireless computer network environment, nodes within the network are connected to one or more AP devices, such as WL 400 Wireless LAN Hardware Access Point available from Compaq Computer Corporation, to form one or more cells of



wireless LAN coverage. IEEE 802.11 stations can also group themselves together to form an *ad hoc* network - a network with no central control and with no connections to the outside world. Here, the network is formed "on the fly," simply because there happen to be mobile devices that have found themselves in proximity to each other and sharing a mutual need to communicate without a pre-existing network infrastructure (e.g., a pre-existing 802.11 BSS with an AP) in the location. An *ad hoc* network might be formed, for example, when people with laptops meet together in a conference room, a train, or a car, and want to exchange data in the absence of a centralized AP. There has been a tremendous recent increase in interest in *ad hoc* networking, as communicating portable devices continue to proliferate.

In the infrastructure mode, an AP device typically includes a transceiver for communicating with at least one node in the wireless network. Once a reliable link between the AP device and the node is established, the node has access to the resources such as email, the Internet, file servers, printers, in the network. The principles of this invention will also apply to other types of networks, such as a home area network (HAN) 132. For example, the wireless station 124 can be taken away from the network 100 in the office to an employee's home, or HAN 132. The HAN 132 is a home network of two computers, wireless station 124 and desktop 134. In one implementation, wireless station 124 is wirelessly connected to AP device 136, forming cell 138. The AP device 136 is connected to the desktop 134 by cables 140 and 142 (e.g., Ethernet or unshielded twisted pair (UTP)) and through hub 144. Alternatively, desktop 134 and wireless station 124 can communicate in the *ad hoc* mode without hub 144 using WNICs as software versions of AP devices. While desktop 134 may provide server services for HAN 132, the two computers may also be connected as a peer-to-peer network, sharing cable modem 146 connecting HAN 132 to the Internet 130.

It should be noted that this implementation of the invention is described in terms of a network comprising AP devices connected to the Internet; however, principles of this invention can also be implemented in a network without AP devices and/or a hub, or a network not connected to the Internet.

FIG. 2 illustrates the communication path from a configuration module 200 to the driver of a WNIC 206 plugged into wireless station 124. The driver 204 acts like a translator between the WNIC 206 and configuration module 200. Each WNIC 206 has its own set of specialized commands that only its driver 204 knows. In contrast, most programs, including configuration module 200 accesses hardware devices by using

generic commands. The driver 204, therefore, accepts generic commands from configuration module 200 and then translates them into specialized commands for the WNIC 206. User library 202 contains specially written functions for configuration module 200. In one implementation, User Library 202 is a dynamic link library.

5           FIG. 3 illustrates a dialog box 300 that appears on the screen of wireless station 124 after a user moves the physical location of station 124 to outside of wireless network 100. Prior to establishing a link, a profile descriptor must be set and the user may manually enter different profiles by pushing the Add button 316 to connect to dialog boxes 400 and 450 of FIGS. 4(A) and 4(B) respectively before starting the automatic  
10       configuration module 200 to reconfigure the WNIC hardware and network parameters for connecting to a new host. Similarly the user may use the Remove button 318 to remove a profile, or the Edit/View button 320 to edit a profile. The user may also force connection to a profile highlighted in the Location Listing 324 section by pushing the Apply button 322. Each profiled AP device in the profile database is shown in the Location Listing  
15       section 324. The project management may give a brief description of the location of the AP device to be associated with the AP device's Single Session Identification (SSID).

Dialog box 300 shows the connection status of the current connection. The name of the current SSID 302 is Dreamspace, representing the string that uniquely describes an AP device currently in use. In order for a group of AP devices to work together, they  
20       must each have unique SSID. In one implementation, each AP device will utilize one channel between the numbers 1 and 11. In the example shown here, AP device Dreamspace is shown in box 306 to operate in channel 7. The choice of the channel of an AP device is set by the administrator of the AP device.

Box 308 represents the transfer speed at which the current AP is talking to the  
25       client. Normally, the transfer speed can be 1, 2, 5.5, or 11 Mbps (mega bits per second). Basically the farther the AP device is from the client, the weaker the incoming signals are and the slower the speed becomes. The AP devices can automatically reduce the speed when the signals can no longer be transmitted at the current speed effectively. The client can choose "Auto" as the value of transfer speed in box 308 to allow automatic speed  
30       selection by the AP device. Alternatively, the client can fix the speed by setting a value of box 308 to command the AP device to communicate at a fixed speed.

The quality of the current link is shown in box 312 as a percentage value; 0% implies that there is no connection. Similarly, the strength of incoming signals is shown in box 314 as a percentage value.

In one implementation, the system provides a software utility that constantly scans the wireless network environment for the presence of a new change. The software utility may reside in configuration module 200. The utility automatically reconfigures the wireless hardware parameters and network configuration parameters in a node when the utility detects changes in the network environment. The automatic switching is made possible by the introduction of profiles. The utility selects the most desirable working profile provided by the user for new parameters when an existing profile is no longer compatible. This invention also may support power saving mode, the status of which is shown in box 306. The wireless AP devices have the ability to run in power saving mode to stop transmitting anything unless there is outgoing data or an incoming signal from the AP device. This mode prolongs battery life.

Each profile will enable the WNIC to establish a connection with the first compatible AP device in the network located by the WNIC. In one implementation, the AP device is located by an autosensing component that transmits profile parameters and waits for verification by compatible AP devices. For each profile, a set of hardware and software/network parameters will be entered into the profile database. Profiles within the profile database may be prioritized or placed in sequential order. Hardware parameters include, but not limited to, SSID, channel, network type, network translation, encryption status, etc. Dialog box 400 can be used to enter hardware parameters as is shown in FIG. 4(A).

Dialog box 400 provides box 400 for the user to associate a unique name with an AP device. Box 402 provides a brief description of the location of the AP device, such as at home or in office X. The user can identify the connection as to an AP device in infrastructure mode in circle 406, or to another wireless card in *ad hoc* mode in circle 408. Transfer speed supported is specified in box 410, and translation status in box 410. Box 410 refers to the encapsulation of the header in the network transport layer. When you transmit a continuous stream of data over the net, such as a file, it is broken into many small chunks of data, such as 1514bytes each. Each chunk is referred to as a packet. Each packet will contain a header to describe the source, destination, routing, protocol and data. Encapsulation or translation describes the standard used the wrap the header. The sample value provided in box 412 is Request for Comments (RFC) 1042. Encryption of data is supported if box 414 is selected.

Software/network parameters that can be specified by the user include, but are not limited to, IP address, network mask, and DNS setting. Network parameters are entered

into the profile database by filling in dialog box 450 of FIG. 4(B). This invention supports dynamic IP address assigned by a Dynamic Host Configuration Protocol (DHCP) server (box 462), or a permanent IP address assigned by the network administrator (box 466). The IP address is written as four sets of numbers separated by periods, for example 192.168.40.3 of box 452. The Subnet mask follows the same format, for example 255.0.0.0 in box 454. The subnet mask helps to identify the computer on the Internet and is determined in part by the IP address1 value in box 452. The identification of the default gateway is entered into box 456 to identify the device on the network that facilitates communication with the Internet 130. The Domain Name System (DNS) translates host name in box 458 and domain name in box 460 into the numeric IP address. DNS service search order is shown in box 464.

This invention addresses the complicated issues of detecting the current wireless network environment and configuring new wireless hardware and network parameters. The detection of the wireless network environment is accomplished by introducing an auto-sensing algorithm. The establishment of a new wireless hardware and network configuration is done through a profile based user/AP device management system. The flow chart of FIG. 6 illustrates how the autosensing algorithm works with the user profile management system to achieve the dynamic reconfiguration effects, is composed of the checking processes in the left column of the flow chart.

The autosensing algorithm starts (step 500) by establishing (step 502) a connection to a selected AP device by sending the parameters associated with the AP device to the driver and issuing a soft boot command to the driver. The selection process may be automatic according to the priorities set in the profile database in one implementation, or the selection process may be done manually by highlighting one of the selections available under the Location Listing section 324 in other implementations. The system will step through the parameters stored in the associated profile in the profile database and communicate with the network based on the selected profile. If the communication is successful, the system will use that profile as the current configuration. Otherwise, it will go to the next profile (step 506) and repeat the same process by going back to step 502. If the system is still connected to the same network/AP device (step 508) as prior to taking the establishing step, and the link quality is still good (step 510), the system sleeps, in one implementation, for three seconds before checking the link quality again. If the link quality is not good, the system returns to step 502 to try to establish another connection.

If, on the other hand, the connection is now to a different AP device, the TCP/IP

settings of the location associated with this AP device are examined (step 514) to reconfigure current network settings. If the TCP/IP settings are static (step 516), the Dynamic Host Configuration Protocol (DHCP) incorporates a much more robust dialogue during lease negotiation. DHCP has seven possible message types that can be used during the IP address assignment sequence. When a DHCP device, such as wireless station 124, attaches itself to the network for the first time, it broadcasts a DHCPDISCOVER packet. A DHCP server on the local segment will see the broadcast and return a DHCPOFFER packet that contains an IP address and other information. The servers may or may not conduct some sort of preliminary testing prior to offering the address to see if the address is already in use by another node somewhere. The client may receive multiple DHCPOFFER packets from any number of servers, so it must choose between them, and broadcast a DHCPREQUEST packet that identifies the explicit server and lease offer that it likes the best. Assuming that the offer is still valid, the chosen server would return a DHCPACK that tells the client the lease is finalized. Therefore, the system waits for DHCPREQUEST packet on the Wireless card driver, releases current IP, and renews current IP by sending a DHCPACK packet to complete the renewing IP process. DHCP provides a framework for passing configuration information to host computers on a TCPAP network and a detailed description of DHCP is provided in RFC 1541, available at <http://www.cis.ohio.state.edu/htbin/rfc/rfc1541.html>, and the entire disclosure of which is incorporated herein by reference.

If the TCPAP setting is dynamic (step 518), the system simply releases current IP and renews current IP without going through the negotiation process.

Through this process of combining autosensing process and profile-based AP management system, users will know when a new AP or network connection is available or the existing AP is not available anymore.

Referring to FIG. 6, it illustrates a block diagram of an exemplary computer (generally designated 600) that may provide a suitable environment within which the principles of the present invention may be implemented and operated. Since the present invention is not limited to application in any particular processing environment, FIG. 6 is illustrative only. Moreover, the principles of the present invention are usable in processing environments other than computer systems, such as data communication (e. g., wired and wireless public and private communication networks) and multimedia networks. Exemplary computer 600 illustratively includes processing circuitry 602 (e.g., at least one conventional processor), conventional volatile memory such as random access

memory 605 and read only memory 610, CPU bus controller circuitry 615, a non-volatile memory (e.g., a removable hard disk drive) 620 controlled by I/O controller 625 via I/O bus 630. Exemplary CPU bus 615 is suitably operative to associate processing circuitry 602, volatile memories 605 and 610, and I/O controller circuitry 625. While exemplary  
5 I/O bus 630 is suitably operative to associate I/O controller circuitry 625, non-volatile memory 620, display device 635 and keyboard 640, or more of a plurality of conventional peripheral devices for communication therewith.

A number of embodiments of the invention have been described. Nevertheless, it will be understood that various modifications may be made without departing from the  
10 spirit and scope of the invention. Accordingly, other embodiments are within the scope of the following claims.

**WHAT IS CLAIMED IS:**

1. A method to configure parameters after a computer is moved to a new location, comprising the steps of:

5           Examining an established link for a need to establish a new link,  
          Establishing the new link by selecting a network profile from a plurality of network profiles stored in a profile database, said network profile containing a plurality of configuration parameters for establishing links; and  
          Reconfiguring parameters automatically without user input for a current  
10 network setting.

2. The method of claim 1, wherein the examining step is repeated once every three seconds.

3. The method of claim 1, wherein the establishing step further comprises testing each network profile from the plurality of network profiles until the new link is  
15 established.

4. The method of claim 1, wherein the establishing step comprises establishing the new link with an access point including issuing a soft boot command.

5. The method of claim 1, wherein the establishing step comprises establishing the new link with a wireless card.

20 6. The method of claim 1, wherein the reconfiguring step further comprises: searching for a dynamic TCP/IP setting for a current location; and if found releasing a current IP; and renewing the current IP.

7. The method of claim 1, wherein the establishing step further comprises:  
25 Searching for a static TCP/IP setting for a current location; and if found  
Releasing a current IP  
Renewing the current IP; and  
Receiving and returning packets from and to a wireless card driver.

8. An apparatus comprising a computer-readable storage medium tangibly  
30 embodying program instructions for configuring a computer after the computer is moved to a new location, the program instructions including instructions operable for causing a computer to:

Examine an established link for a need to establish a new link,  
Establish the new link by selecting a network profile from a plurality of

network profiles stored in a profile database, said network profile containing a plurality of configuration parameters for establishing links; and

Reconfigure a current network setting.

5       9.     The apparatus of claim 8, wherein the program instructions further comprise instructions to cause the computer to examine the established link once every three seconds.

10       10.    The apparatus of claim 8, wherein the program instructions further comprise instructions to cause the computer to test each network profile from the plurality of network profiles until the new link is established.

11       11.    The apparatus of claim 8, wherein the program instructions further comprise instructions to cause the computer to establish the new link with an access point by issuing a soft boot command.

12       12.    The apparatus of claim 8, wherein the program instructions further comprise instructions to cause the computer to establish the new link with a wireless  
15   card.

13       13.    The apparatus of claim 8, wherein the program instruction to cause the computer to reconfigure further comprises instructions to:

search for a dynamic TCP/IP setting for a. current location;

release a current IP; and

20       renew the current IP.

14       14.    The apparatus of claim 8, wherein the program instruction to cause the computer to reconfigure further comprises instructions to:

search for a static TCP/IP setting for a current location;

Release a current IP;

25       Renew the current IP; and

Receive and return packets from and to a wireless card driver.

15       15.    A computer readable memory which includes a reconfiguration apparatus comprising:

30       A profile database to store a plurality of network profiles containing reconfiguration parameters for reconfiguring a network environment for a node in a network after the node is relocated to a different location;

A detection process to examine the quality of an established link on a node; and

A selector process, operatively connected to the profile database, to



select, in response to a signal from the detection unit, a next profile from the profile database for establishing a suitable network environment for the node.

16. The apparatus of claim 15, wherein the reconfiguration parameters comprise SSID.

5 17. The apparatus of claim 16, wherein the reconfiguration parameters further comprise associated address and channel.

18. The apparatus of claim 15, wherein the reconfiguration parameters comprise IP address, subnet mask, and gateway.

10 19. The apparatus of claim 18, wherein the reconfiguration parameters further comprise domain name and DNS address.

20. The apparatus of claim 15, wherein the node communicates with other nodes in the network through access points.

21. The apparatus of claim 15, wherein the node communicates with other nodes in the network in an *ad hoc* mode.

15 22. The apparatus of claim 15, wherein the node supports encrypted information.

23. The apparatus of claim 15, wherein the node runs in power saving mode.

24. The apparatus of claim 15, wherein the plurality of network profiles in the profile database is prioritized.

20 25. A computer readable memory which includes a reconfiguration apparatus comprising:

An auto-sensing process to detect changes in a network environment by checking for a connection, an AP device and a quality of the connection; and

25 A user profile management process to step through automatically a plurality of parameters associated with a selected profile to communicate with the network based on the plurality of parameters.




FIG. 1




FIG. 2




FIG. 3

**Add New Profile**

Wireless LAN | Network Setup/IPv4

Location Profile

Please enter the SSID for this location. (Max 32 characters)

Please enter the description for this location. (For example: My home)

Connect to:

☐ Access Point

☐ Another Wireless Card

Speed (Mbps): **Full Auto**

Encryption:

☐ Scramble Traffic for IPv4

☐ Enable Power Saving Mode

☒ Auto search for this model if current IP is dropped

Channel: **RFC 1042**

OK Cancel

Handwritten labels: 36, 38, 114, 400, 402, 404, 410, 412

FIG. 4(A)

**Add New Profile**

**Wireless Network Profile**

If you use DHCP, an IP address will automatically be assigned to the network card. Contact your administrator to manually assign an IP address.

- ☐ Use DHCP to assign IP automatically.
- ☐ Set static IP address manually.

IP Address: 192.168.1.2

Subnet Mask: 255.255.255.0

Default Gateway: 192.168.1.1

Domain Name System (DNS)

Host Name: mycomp1 Domain: Sybergen.com

DNS Service Search Order

100.0.190

UP DOWN

ADD EDIT REMOVE

Domain Suffix Search Order

UP DOWN

ADD EDIT REMOVE

OK Cancel

Handwritten annotations: 450, 452, 454, 456, 460, 66, 8, 64

FIG. 4(B)




FIG. 5




FIG. 6



# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 01/04829

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04L29/06

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, INSPEC

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 99 46890 A (NOMADIX INC) 16 September 1999 (1999-09-16) page 2, line 1 -page 4, line 17 page 13, line 20 -page 14, line 14 -----	1, 8, 15, 25

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

'A' document defining the general state of the art which is not considered to be of particular relevance

'E' earlier document but published on or after the international filing date

'L' document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

'O' document referring to an oral disclosure, use, exhibition or other means

'P' document published prior to the international filing date but later than the priority date claimed

'T' later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

'X' document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

'Y' document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

'&' document member of the same patent family

Date of the actual completion of the international search

25 June 2001

Date of mailing of the international search report

05/07/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl.

Authorized officer

# INTERNATIONAL SEARCH REPORT

Int'l Application No  
PCT/US 01/04829

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9946890 A	16-09-1999	US 6130892 A	10-10-2000
		AU 3077199 A	27-09-1999
		EP 1076959 A	21-02-2001
<hr/>			

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record.**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**